

[54] **INTRAOCULAR LENS**

[76] **Inventor:** **Dennis T. Grendahl**, Excelsior Bay
Gables, Excelsior, Minn. 55331

[21] **Appl. No.:** **938,071**

[22] **Filed:** **Dec. 4, 1986**

[51] **Int. Cl.⁴** **A61F 2/16**

[52] **U.S. Cl.** **623/6**

[58] **Field of Search** **623/6**

[56] **References Cited**

U.S. PATENT DOCUMENTS

4,159,546	7/1979	Shearing	623/6
4,439,873	4/1984	Poler	623/6
4,562,600	1/1986	Ginsberg et al.	623/6
4,605,409	8/1986	Kelman	623/6
4,657,546	4/1987	Shearing	623/6

FOREIGN PATENT DOCUMENTS

2124500A	2/1984	United Kingdom	623/6
----------	--------	----------------	-------

OTHER PUBLICATIONS

Lens Styles from Cilco (Advertisement Brochure)

Cilco, Inc. 6 pages, style SK-4 on page 4 relied upon, Oct. 1982, pp. 1, 4 and 6 cited.

Primary Examiner—Ronald L. Frinks
Attorney, Agent, or Firm—Hugh D. Jaeger

[57] **ABSTRACT**

A light weight intraocular lens for placement in a capsular bag, including a small hard inner lens optic and a soft pliable skirt surrounding the lens optic. The lens optic is a bi-convex optic. The lens optic is a high refractive index material and has a diameter of about 2-4 mm and utilizes a laser discission yag space. The soft pliable skirt with an inner circumference channel secures about an edge of the lens optic and extends away at a downwardly sloping angle. The bottom edge of the skirt can be continuous or intermittent, and can include a single or dual ridge barrier. The outer diameter of the lens skirt can be up to 8-9 mm.

6 Claims, 3 Drawing Sheets

